

90° room surveillance



180° room surveillance



3 elevators in an overview



3 elevators in an overview

Fits In. Watches Out.

Inconspicuous surveillance with state-of-the-art technology. The D24 FixDome from MOBOTIX adapts perfectly to any task. Exchangeable lenses, various mounting and configuration options including vandalism set support unlimited application possibilities.



HiRes Video

MOBOTIX HiRes video replaces up to 6 cameras ...

- Attractively designed FixDome camera featuring exchangeable lenses from Tele to Wide Angle
- Numerous installation options both indoor and outdoor
- On-wall set with space for extension modules (battery, UMTS, WLAN, etc.)
- Integrated DVR with HiRes video recording (4 GB MicroSD card incl.)
- Robust, low-maintenance and weatherproof from -30 to +60 °C (-22 to +140 °F), (IP65)
- Digital continuous zoom, pan and tilt
- Can be upgraded to an intercom system with the MOBOTIX ExtIO module

... starting at 448 €* incl. video management software


*MSRP (Manufacturer's suggested retail prices) • Prices ex-works Langmeil, Germany (EXW) • Excluding VAT and any other handling charges • Information subject to change without notice! • © MOBOTIX AG

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG • D-67722 Langmeil • Tel: +49 6302 9816-103 • Fax: +49 6302 9816-190 • sales@mobotix.com

Technical Specifications D24



The HiRes Video Company

Technical Specifications D24 MonoDome	
Models	Basic, IT, IT-Night, Sec, Sec-Night
Lenses	22 to 135 mm format, horizontal angle 90° to 15°
Sensitivity	Color: 1 lux (t=1/60 s), 0.05 lux (t=1/1 s) B/W: 0.1 lux (t=1/60 s), 0.005 lux (t=1/1 s)
Sensor	1/2" CMOS, progressive scan
Max. image resolution	Color: 2048 x 1536 (3MEGA), B/W: 1280 x 960 (Mega)
Image format	2048 x 1536, 1280 x 960, 1024 x 768, 800 x 600, 768 x 576 (D1), 704 x 576 (TV-PAL), 640 x 480, 384 x 288, 352 x 288, 320 x 240, 160 x 120; free image format selection (e.g. 1000 x 200 for skyline)
Max frame rate (M-JPEG) (Live/Recording)	VGA: 25 fps, TV-PAL: 18 fps, MEGA: 8 fps, 3MEGA: 4 fps
Video stream (MxPEG) (Live/Recording/Audio)	VGA: 30 fps, TV-PAL: 30 fps, Mega: 30 fps, 3MEGA: 20 fps
Image compression	MxPEG, M-JPEG, JPEG, H.263 (only Video-VoIP)
Internal DVR	MicroSD slot (camera-internal video recording up to 32GB)
External storage	Directly on NAS and PC/Server without additional recording software
Software (inclusive)	Video management software MxEasy, Control room software MxControlCenter
Image processing	Backlight compensation, automatic white balance, image distortion correction, video sensor (motion detection)
Virtual PTZ	Digital Pan/Tilt/Zoom, continuous 8x zoom
Alarm/Events	Triggering of events by integrated multiple-window motion detection, external signal, temperature sensor, notification over email, FTP, IP telephony (VoIP, SIP), visual/acoustic alarm, pre- and post-alarm images
Audio	Optional via ExtIO, lip-synchronous audio, two-way speaker, audio recording, video VoIP supported
Interfaces	Ethernet 10/100, USB, MxBus
Video phone	VoIP, SIP, two-way speaker, remote control via DTMF signaling, event notification
Security	User-/Group management, HTTPS/SSL, IP address filter, IEEE 802.1x, intrusion detection, digital image signature
Certificates	EMC (EN50121-4, EN55022, EN55024, EN61000-6-2, FCC part15B, AS/NZS3548)
Power supply	Power over Ethernet (IEEE 802.3af): PoE class variable depending on operating mode; power consumption: typ. 3 W; with PoE switch/MOBOTIX PoE adapter
Operating conditions	IP65 (DIN EN 60529), -30 to +60 °C (-22 to +140 °F)
Dimensions	Ø x H: 16 x 8.6 cm Weight: ca. 350 g
Standard delivery	Housing (high-resistance composites – PBT-PC), white, shockproof polycarbonate dome (transparent), free choice of lenses, mounting parts, allen wrench, patch cable, manual, software, 4 GB MicroSD (except Basic)

Technical information subject to change without notice.

Available Accessories D24 MonoDome					
<p>In-Ceiling Set MX-OPT-IC</p>  <ul style="list-style-type: none"> Consists of in-ceiling mount and mounting parts Easy mounting from front Ø 150 mm installation dimension It can be ordered with stainless steel cover 	<p>On-Wall Set MX-OPT-AP</p>  <ul style="list-style-type: none"> Consists of On-Wall mount and mounting parts Protects the cabling 165 mm x 37 mm 	<p>Vandalism Set MX-D24M-Vandal-ESMA</p>  <ul style="list-style-type: none"> Reinforced dome (3 mm Polyc.) Stainless steel vandalism housing polished or matt, in white, silvergray or black 	<p>Outdoor Wall Mount MX-OPT-WH</p>  <ul style="list-style-type: none"> Weatherproof (IP65) Covers RJ45 wall outlets Space for expansion modules (WLAN) 	<p>Pole Mount MX-OPT-MH</p>  <ul style="list-style-type: none"> 3 mm stainless steel, white 2 stainless steel straps for pole diameter 60-180 mm, incl. mounting parts 	<p>ExtIO Extension Module MX-ExtIO</p>  <ul style="list-style-type: none"> Microphone/Speaker PIR sensor for motion detection, temperature sensor Switch in-/outputs

	L22 Super Wide Angle 90°	L32 Wide Angle 60°	L43 Wide Angle 45°	L65 Tele 31°	L135 Tele 15°
Lenses					
	approx. 90°H x 67°V at 10 m appr: 20.0 x 13.3 m	approx. 60°H x 45°V at 10 m appr: 11.5 x 8.2 m	approx. 45°H x 34°V at 10 m appr: 8.2 x 6.1 m	approx. 31°H x 23°V at 10 m appr: 5.5 x 4.0 m	approx. 15°H x 11°V at 10 m appr: 2.6 x 1.9 m

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG • D-67722 Langmeil • Tel: +49 6302 9816-103 • Fax: +49 6302 9816-190 • sales@mobotix.com